



The Carbon Dioxide detection solution

PS500-CO2



Designed by our customers, this robust and accurate gas detector provides unrivalled protection in confined space applications.

- 0-5% Carbon Dioxide (CO₂) detection
- NDIR sensing technology
- Large font for easy reading
- Piercing 95 dB audible plus 360-degree high-visibility light bar
- On-board datalogging for calibration certificates, data management, and event logging
- High impact rubberised case
- IP65
- Low cost of ownership

Detection, Protection, Innovation



GMI. CONFIDENCE WHERE SAFETY IS CRITICAL. Gas Measurement Instruments designs, manufactures and markets a wide range of the highest quality proven personal portable and fixed gas monitoring systems. GMI is an international brand with a worldwide network of distributors and dedicated service centers ensuring fast and effective turnaround on instrument calibration and repair. Our uncompromising engineering excellence, established in over half a century of leadership, enables us to meet the exacting demands of industries where safety is critical. By building and maintaining strong relationships with our customers, GMI understands the unique challenges of the diverse markets we serve. Today, our proud heritage of pioneering gas leak monitors and detectors is shaping the future of GMI.



PS500-CO2



The PS500-CO2 detects 0-5% volume CO₂ reliably and accurately using infrared capabilities.

The large display font allows for easy measurement reading.

The PS500-CO2 is particularly useful in noisy environments, featuring a very loud (95dBA) penetrating and distinctive audible alarm together with high visibility large area visual alarm.

Sampling type: diffusion for confined space working.

A robust, moulded, rubberised casing guaranteeing Hi-Impact resistance, the PS500-CO2 can be used in the most demanding industrial environments.

TECHNICAL SPECIFICATION	
Size:	140 x 85 x 45 mm / 5.5" x 3.3" x 1.7"
Weight:	0.4 kg / 14 oz.
Humidity:	0-98% non condensing
Alarms:	Visual 360° full light bar, piercing 95db audible 4 gas alarms per gas user programmable TWA/STEL alarms visual and audible Flow fault visual and audible Low battery alarm
Display:	LCD backlight display
Datalogging:	Timed: 24 hours of timed logs at 1 log per minute Session: Minimum of 180 logs Calibration: Minimum of 8 calibration logs
Battery:	NiMH rechargeable battery—12 hr. minimum
Enclosure:	High impact rubberised polycarbonate case
Rating:	IP65 (Dust tight and water resistant)
Approvals:	CE0518 ATEX II 2 G EEx iad IIC T3
IECEx:	EEx iad IIC T3
Warranty:	2 years

SENSOR SPECIFICATION				
GAS	RANGE	RESOLUTION	SENSOR TYPE	T90
CO ₂	0-5% V	0.05% V	NDIR	25 sec

ORDERING INFORMATION AND ACCESSORIES	
61371P	PS500-CO2 Instrument The instrument is supplied calibrated and complete with: - Charger (Universal plug) - Battery / sensor grille key - User CD - Quick operation guide
66028	Neck harness
61208	Datalogging package
66083	Sensor grill hydrophobic filter
66084	Sensor gas inlet filter
66206	Car/vehicle charge 12/24V
61502	Automatic Bump / Calibration Station
For a comprehensive list of accessories, contact your local distributor, or alternatively, GMI Ltd.	



GMI Headquarters
Inchinnan Business Park
Renfrew
PA4 9RG
Scotland
Tel: +44 (0) 141 812 3211
Fax: +44 (0) 141 812 7820
sales@gmiuk.com
www.gmiuk.com

Service and Calibration - UK
25 Cochran Close
Crownhill
Milton Keynes
MK8 0AJ
Tel: +44 (0) 1908 568 867
Fax: +44 (0) 1908 261 056
service@gmiuk.com
www.gmiuk.com

Service and Sales - USA
4055 Technology Forest Blvd.
The Woodlands, TX 77381
Tel: (713) 559-9290
Toll free: (888) 367-4286
Fax: (281) 292-2860
sales@detcon.com
www.detcon.com

Distributed by:

As an ISO 9001 approved company, Gas Measurement Instruments quality assurance programmes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.